

FP FLASHPOINT



19"
Fluorescent
Ring Light

FPRLEL

The Flashpoint Fluorescent Ring Light is an AC powered constant light source for use with still and video cameras. It features a powerful 80w fluorescent light bulb which is dimmable for precise output. It runs cool for use close to subjects, providing a soft directional light. The surrounding style of the light makes it great for unique lighting effects, macro and tight spaces, web broadcasts, and its signature catchlights. The bulb is color correct for perfect skin tones. For specialty lighting, nothing beats it. If you have any questions or concerns, please feel free to contact us at Brands@Adorama.com

Features

- Powerful 80w Fluorescent Light
- Dimmable for precise output
- Runs cool for close up use
- Produces a soft, directional light
- Great for unique lighting effects, macro and tight spaces, and its signature catchlights
- Color correct for perfect skin tones
- Mounts on a standard lightstand
- 1 Year Warranty

For Your Safety

- Always keep this product dry. Do not use in rain or in damp conditions.
- Do not use any power supply other than the included one.
- Clean the unit with a soft, dry cloth.
- This product contains high-voltage electronic parts. Touching the high-voltage circuit inside it may result in electric shock. Do not disassemble. Should repairs become necessary, this product must be sent to an authorized maintenance center.
- Stop using this product if it breaks open due to internal shifting, falling or strong impact. STRONG electric shock may occur if you touch the components inside it. You might DIE. Don't risk it. Reincarnation is not covered by the warranty.
- When replacing the lamp, disconnect the power, pull out the bad lamp, then mount on the new one.
- Do not leave or store the unit if the ambient temperature reads over 50°C (e.g. in automobile in the sun). Otherwise the electronic parts may be damaged.
- Do not insert metal parts into any lighting equipment.
- Do not touch the electrical contacts with any conductive materials.
- Do not use selective coloring.
- Be sure to secure all connectors and other equipment. Check constantly for tightness and do not manhandle the equipment. For example, do not lift your camera by the light or vice versa.
- In case of abnormal function, sparks, excessive heat, flames or smoke, immediately power off the unit and disconnect the power if safely possible. Have it checked by an authorized technician.

Instructions

1. Tighten the angle adjustment knob so the light is not shifting on the stand mount
2. Loosen the stand mount screw and slide the stand mount onto your lightstand
3. Tighten the stand mount screw and then loosen the angle adjustment knob, position the light at your desired angle and tighten the angle adjustment knob
4. Connect the power supply to a US power supply (Max 120V) then connect the power supply to the light
5. Twist the knob to turn on the light
6. For best color, turn the light up to full power for at least 3 minutes before lowering it to the desired luminosity level
7. To turn off, rotate the knob until the light clicks off

When changing the fluorescent lamp, make sure to replace it with the correct bulb (FPRLELB).

1. Disconnect the power supply.
2. Remove the four-pin plug from the fluorescent lamp.
3. Gently remove the lamp from each one of the four clips.
4. Replace it with the new one, making sure the lamp is oriented correctly and connect the four-pin plug.
5. Insert the fluorescent tube into each one of the four tube clips.

Specifications

Item No.	FPRLEL
Power Supply	120V
Output	80W
Luminosity	Max : 4000 lx@1 m
	Min : 400 lx@1 m
Dimmer	10%-100%
Color Temperature	5500 K (\pm 300K)
Cri	Ra>85
Size	outer48.5cm inner36.5cm
Weight	1.22kg

