

Godox 神牛

SL系列摄影灯

SL Series Video Light



深圳市神牛摄影器材有限公司

地址/Add: 深圳市宝安区福永镇福海大道西新和村华发工业园A4栋
2/F, Building A4, Xinhe Huafa Industrial Zone, Fuhai RD West,
Fuyong Town, Baoan District, Shenzhen 518103, China
电话/Tel: +86-755-29609320(8062) / +86-755-25726373
传真/Fax: +86-755-25723423
邮箱/E-mail: godox@godox.com

82.A0000SL0-00

Instruction manual | 说明手册

Chinese English Bilingual | 中英文双语

产品参数

| 摄影灯 | 白光版SL-100W | 黄光版SL-100Y |
|--------------|----------------------|------------|
| AC电源供电 | AC 100~240V 50/60Hz | |
| 频道 | 16个 | |
| 组别 | 6组(A, B, C, D, E, F) | |
| 功率 | 100W | |
| 色温 | 5600K±300K | 3300K±300K |
| 100%光照度(LUX) | 2400(1米) | |
| 100%光通量(Lm) | 13000 | |
| 显色指数 | 90-92 | |
| R9 | 50-60 | |
| 调光范围 | 10%~100% | |
| 工作环境温度 | -10~50度 | |
| LED灯珠安全温度 | ≤70°C | |
| 产品尺寸 | 34x23x13cm(不含灯头保护罩) | |
| 净重 | 约2.41kg | |

| 遥控器 | RC-A5 |
|--------|----------------------|
| 供电 | 3.0V(AAA*2)(不包含) |
| 无线频率 | 433MHz |
| 距离(空旷) | ≥20米 |
| 频道 | 16个 |
| 分组遥控 | 6组(A, B, C, D, E, F) |
| 待机时间 | 1年以上 |
| 工作环境温度 | -10~50度 |
| 产品尺寸 | 120mm*38mm*15mm |
| 净重 | 30g |

设计和规格如有变更，恕不另行通知。

Foreword:

Thank you for purchasing this Godox Product!

SL Series video lights are excellent for product shooting, photojournalistic and video recording, etc. It creates stable light resource and even illumination for photography. Two models are available: White Version (5600K), Yellow Version (3300K).

Features:

- 100W LED bulbs guarantee high light brightness
- The color rendering index is over 90 and R9 is over 50, presenting the objects authentically
- Wirelessly adjust light brightness
- Wireless 433MHz grouping system (6 groups & 16 channels)
- Large-sized LCD panel. Settings auto saved
- With temperature control function to prevent overheating
- With specialized protect cover to protect the LED beads
- With red copper heatsink and built-in fan to offer excellent heat dissipation

| Type | Model |
|---|---------|
| White Version(Color Temperature 5600K) | SL-100W |
| Yellow Version(Color Temperature 3300K) | SL-100Y |

For your safety:

- ⚠ Do not place in high temperature or high humidity conditions.
- ⚠ If this product overheats, it will cease operation and resume working after cooling down. This is due to the built-in overtemperature protection.
- ⚠ Do not handle with wet hands, immerse in water, or expose to rain.
- ⚠ Do not disassemble or modify this product. Should the product break open as the result of a fall or other accident, send the defective back to authorized service center for inspection and maintenance.

Parts




Body

01. LED Beads
02. Protect Cover
03. Heatsink
04. Accessory Slot
05. ON/OFF Power Switch
06. Select Dial + SET Button
07. CH/GRP Button
08. AC Power Jack
09. Antenna
10. LCD Panel (White in Blue)
11. Mounting Bracket
12. Umbrella Input
13. Direction Adjusting Handle

Remote Control:

01. LCD Panel (Black in White)
02. Power Switch
03. CH/GRP Button
04. SET Button
05. "-" Button
06. "+" Button
07. Battery Compartment Cover



Accessories



Remote Control

Standard Reflector

Lamp Cover

Power Cord

Operation

Using the Video Light

- Connect the light with AC power jack.
- Press the ON/OFF Power Switch, the video light begins to giving out light.
- LCD panel shows the information.

Light Brightness Adjustment

- Turn the select dial to adjust the light brightness.
- The light brightness adjustable range is at 10%~100%.

Temperature Indication

- This video light checks its temperature at any time to avoid dangerous situations. It will auto power off when the temperature is too high.
- Press the SET button for 2 seconds and the temperature can be switched between Celsius and Fahrenheit.

Wireless Remote Control

With 433 MHz wireless system, this product has remote grouping and control function. Up to 6 groups of video lights can be controlled. 16 channels are available with strong anti-interference capability.

- Please set the channels and groups of video light to the same as those of remote control before usage.
- When using the White Version, please set the color temperature of the remote control as 5600K constantly;
- When using the Yellow Version, please set the color temperature of the remote control as 3300K constantly;

Adjusting Channel/Group of the Video Light

- Press the CH/GRP button and the group icon blinks. Turn the select dial to choose a group ID (A to F).
- Press the CH/GRP button twice and the channel icon blinks. Turn the select dial to choose a channel ID (1 to 16).

Adjusting Channel/Group of the Remote Control

- Press the CH/GRP button and the group icon blinks. Press the“-”“+” button to choose a group ID (A to F).
- Press the CH/GRP button twice and the channel icon blinks. Press the“-”“+” button to choose a channel ID (1 to 16).

Adjusting Light Brightness/Color Temperature with the Remote Control

- Press the“-”“+” button to adjust the light brightness.
- Press the SET button of the remote control once and the color temperature icon blinks. Press the“-”“+” button to adjust the color temperature.

Other Operation Tips:

- Pressing the ON/OFF button on the remote control can turn on/off all the video light groups.
- Pressing the “SET” button on the remote control for 2 seconds can turn on/off the current video light group.
- Please remove the battery if the light will not be used for an extended period of time.



When there are some abnormal situations in the inner video light, the relevant LCD signs will blink as warnings. For example:

1. When the fan stops working due to fault, the LCD signs will blink to alarm.
2. When heatsink' temperature is over 70 Celsius degrees, the temperature on the LCD panel will blink and the video light will stop working.

Technical Data:

| Video Light | White Version SL-100W | Yellow Version SL-100Y |
|------------------------|--|------------------------|
| AC Power Supply | AC 100~240V 50/60Hz | |
| Channel | 16 | |
| Group | 6 groups (A, B, C, D, E, F) | |
| Power | Max. 100W | |
| Color Temperature | 5600K±300K | 3300K±300K |
| 100% Illuminance (LUX) | 2400 (1m) | |
| 100% Luminous Flux | 13000 | |
| Color Rendering Index | 90-92 | |
| R9 | 50-60 | |
| Light Brightness Range | 10%~100% | |
| Operation Temperature | -10~50°C | |
| Safe Temperature | ≤70°C | |
| Dimension | 34x23x13cm (Not included the Lamp Cover) | |
| Net Weight | Approx. 2.41kg | |

| Remote Control | RC-A5 |
|-----------------------|----------------------------|
| Power Supply | 3.0V(AAA*2)(not include) |
| Wireless Frequency | 433MHz |
| Distance(emptyness) | ≥20m |
| Channel | 16 |
| Group | 6 groups(A, B, C, D, E, F) |
| Standby Time | Over one year |
| Operation Temperature | -10~50 °C |
| Dimension | 120mm*38mm*15mm |
| Net weight | 30g |

* Product design and specifications are subject to change without notice.