# CS6 Series selector switch w/wall plate

Wall-mount selector switch for on/off control of up to six program sources is a two pole rotary with "Euro-Style" screw inputs. It's ideal for program source selection in medical offices, mixed-use retail suites, schools, hotels, restaurants and residential applications where source selection without volume control adjustment is desired (where volume adjustment is accomplished at the source).

### **Features**

- Six inputs for remote source selection
- Screw terminal input connections; pigtail output connections
- May be used in conjunction with a 70/25V volume control (such as Lowell 25W, 50W or 100W LVC Series

   order separately) by connecting selector output to attenuator input. Selector and volume control may then be mounted side by side in a two-gang E.O. box or in separate single gang boxes.
- Choice of one-gang plate (standard or decorator style; stainless steel, white, stainless steel & white, stainless steel & black)
- Matching knobs and mounting screws
- Mounting depth is 1" for convenient installation into a standard electrical outlet box or Lowell surface mount box No. P1X (order separately).





CS6-SS

CS6-DW







CS6-DSW

# A&E Specifications

The source selection device shall be Lowell Model \_\_\_\_\_, which shall be a six input selector switch with \_\_\_\_\_ (standard, decorator style) 1-gang wall plate in \_\_\_\_\_ (stainless steel, white, stainless steel & black, stainless steel & white) with matching knobs and mounting screws. The selector switch shall be two-pole rotary style for isolation between lines. Wiring connections

shall be to screw terminals allowing the unit to be field connected as an independent selector for use with a volume control. The wall plate shall measure 2.75"W x 4.5"H x 1"D for installation into a standard gang size E.O. box (not included).

### Model Summary

Model No.	Description	Selector Switch	Selector Connections	Assembly Size (in)	Wall Plate Size	Wall Plate Style	Wall Plate Color
CS6-SS	6 position selector	2-pole, rotary	Euro style screw	2.75 x 4.5 x 1	1-gang	standard	stainless steel
CS6-DW	6 position selector	2-pole, rotary	Euro style screw	2.75 x 4.5 x 1	1-gang	decorator	white
CS6-DSB	6 position selector	2-pole, rotary	Euro style screw	2.75 x 4.5 x 1	1-gang	decorator	stainless steel & black
CS6-DSW	6 position selector	2-pole, rotary	Euro style screw	2.75 x 4.5 x 1	1-gang	decorator	stainless steel & white



## **Typical Application and Schematic**

