

Model No.

LV-5K

Potentiometer Volume Control

INCLUDES:

- Potentiometer volume control
- 1-gang standard wall plate
- Rotary knob



POTENTIOMETER VOLUME CONTROL with 5k ohm impedance provides economical volume level adjustment in systems with low power circuits. This unit includes a standard one-gang stainless steel wall plate with black rotary knob.

FEATURES

DESCRIPTION: Potentiometer volume control for applications with constant voltage, 25V/70V loudspeaker systems

RESISTANCE: 5000 ohm

POWER RATING: 5W audio

SWITCH TYPE: Fluted rotary knob, black

ATTENUATION: Continuous attenuation — no stop at minimum or maximum

WALL PLATE: One-gang standard wall plate, stainless steel. 2.75 in. x 4.5 in. with stamped and filled dial scale

COUNTRY OF ORIGIN: Assembled in U.S.A. (U.S. stainless steel wall plate, Chinese components)

A&E SPECIFICATIONS

The potentiometer volume control with 5k ohm impedance shall be Lowell model LV-5K, which shall include a standard one-gang stainless steel wall plate with stamped and filled dial scale (0, Max), black fluted rotary knob, and mounting screws. It shall feature continuous attenuation with no stops.

LV SERIES OVERVIEW

Model No.	Power Rating	Resistance	Steps	Switch Type	Style	Color	For Use With
LV-50S	5W audio	50 ohm	continuous	rotary knob	1g standard wall plate	ss	voice coil circuits
LV-50S-RM	5W audio	50 ohm	continuous	rotary knob	adhesive label	black	voice coil circuits
LV-5K	5W audio	5k ohm	continuous	rotary knob	1g standard wall plate	ss	25/70V speaker line

THIS SPEC

DRAWINGS

