

---

## Owner's manual and pro tips:

---

- High impedance INPUT optimizes electric-guitar pickup tone, for direct-PA or recording hookups.
- GAIN is clean over most of its range, but yields rich chewy Quilter overdrive in the last 10% of it's range.
- Single powerful TONE control adjusts both mids and highs to go from mellow to crisp.
- MASTER provides overall volume control, including any overdrive.
- Switchable CAB SIM warms up the tone for electric guitar, or select FRFR for full range sources such as keys or piezo pickups. PRO TIP: use the CAB SIM to "electrify" the tone of an acoustic guitar for better results with pedals.
- XLR output interfaces with normal balanced Mic inputs.
- Uses 48V phantom power when available, or 9V pedal supply, or remove the bottom cover to add a 9V battery.
- The 9V battery (if used) is controlled by the 9V BAT position on the power switch. Set to EXT PWR when not in use. The unit is always active when connected to phantom power or a 9V pedal supply. Turn down Master to change guitars, etc.



**WARNING:** Phantom powered devices normally generate significant on/off and plug/unplug noises.

**MUTE** the mic channel before changing connections.

**Quilter**<sup>™</sup>  
Amplification est. 1968

THE ULTIMATE **ELECTRIC** DIRECT BOX

QUILTERLABS.COM