



## ROTOLIGHT AEOS 2



MOVE. SHOOT. CREATE



16.7 MILLION COLOURS (RGBWW)



2500 DIGITAL FILTERS



INTUITIVE TOUCHSCREEN

DISPLAY




NATIVE IOS & ANDRIOID APP













ULTIMATE KIT

RL-AEOS2-ULKIT



**MASTERS KIT** 

**RL-AEOS2-MASTERS** 



**EXPLORER KIT** 

RL-AEOS2-EXP

## **AVAILABLE BUNDLES**

## "THESE LIGHTS HAVE CHANGED MY PHOTOGRAPHY AND THEY CAN CHANGE YOURS TOO"

JASON LANIER - MASTER OF LIGHT

## **TECHNICAL SPECIFICATIONS**

With the AEOS 2, the world is your studio.
Combining the shoot what you see benefits of powerful continuous light with a High Speed RGBWW strobe, AEOS 2 offers unmatched versatility for photographers and filmmakers. Uniquely lightweight with an ultra-thin design, it's never been easier to achieve beautiful soft light on the move.

TECH	SPECS		
Peak Output (Lux) @ 3ft	11,500 (continuous) 17,500 (flash)		
Lux at 3ft F-stop at ISO 100/200/400	11,500 F13/ F18/ F22		
Lux at 6ft F-stop at ISO 100/200/400	2940 F6.3/ F9/ F5		
Lux at 9ft F-stop at ISO 100/200/400	1420 F3.5/ F4.5/ F6.3		
TLCI	95		
CRI	95		
Power Consumption	120W		
Battery Type	V-lock / DC 24V 150W		
Mounting	1/4" - 20 tripod or optional Yoke		
Dimensions	W: 295mm (11.5") x D 25mm (1")		
Wireless Control	WIFI & Bluetooth via IOS & Android app		
Beam Angle	50 degrees		
Max Shutter Speed Sync	1/8000th		

-	Brightness at 1m (peak output)						
20K _							
15K							
10K							
5K							
-	Rotolight AEOS 2 (Flash)	Rotolight AEOS 2 (Continuous)	Aputure Nova P300c	Litepanel Gemini 1x1 Soft	Luxli Timpani 1x1 RGBWW		

	Rotolight AEOS 2	Aputure Nova P300c	Litepanel Astra 6X Bi	Litepanel Gemini 1x1Soft	Luxli Timpani 1x1 RGBWW
Touchscreen Interface	~	×	×	×	×
Electronic Diffusion	~	×	×	×	×
High Speed Sync Flash	~	×	×	×	×
Peak Brightness (1m)	9230 lux	9000 lux	2651 lux	5544 lux	3430 lux
Digital Filters	2500	300	×	600	150
Colour Accuracy TLCI	99	95	95	97	95
Weight	1.4kg	10.35kg	3.2kg	5.31kg	3.15kg
Power Consumption	120W	360W	105W	200W	120W