Tender HAMMERTONE

tesetp

DC POWER CONNECTOR **OUTPUT JACK INPUT JACK** DAMP TIME TONE LEVEL tesetp ** ← LED Jender Tender

FOOTSWITCH

Fender

HAMMERTONE REVERB

Thanks for purchasing the Hammertone Reverb a classic effect that adds richly resonant depth, dimension and atmosphere to your sound.

Enter a world of ringing reverb possibilities with time, damp, and level controls, and use the Type and Tone switches to tailor the tonal character even more, including hall, room and plate reverb modes. Reverb is a time-honored essential in the arsenal of any guitarist, and the Hammertone Reverb puts this sonorous sound at your feet in every shade from delicate to drenched.

OUTPUT JACK

Low-impedance output connects to amp or next pedal in signal chain.

INPUT JACK

High-impedance input for electric guitar, bass, acoustic guitars with pickup systems, keyboards and other instruments.

DC POWER CONNECTOR

Connect DC adapter here. Standard center-negative 9VDC jack for use with appropriate power supplies.

TIME CONTROL KNOB

Adjusts reverb decay time.

DAMP CONTROL KNOB

Adjusts the amount of high-end "shimmer" in the reverb effect. Higher settings damp the effect more for a darker reverb sound; lower settings let top end ring out for a brighter sound.

LEVEL CONTROL KNOB

Adjusts volume of reverb signal.

TYPE SWITCH

Three-position switch for Hall (up), Room (middle) and Plate (down) reverb types.

TONE SWITCH

For normal (up) and dark mode (down). Dark mode rolls off treble, letting reverb sit more easily in some mixes.

LED

Illuminates when effect is on.

FOOTSWITCH

Turns effect on and off.





A PRODUCT OF

CORONA, CALIFORNIA, U.S.A.

Fender® is a registered trademark of FMIC.

Copyright © 2022 FMIC. All rights reserved.

PN 7724435000 REV C

IMPORTANT SAFFTY INSTRUCTIONS

- WARNING: To prevent damage, fire or shock hazard, do not expose the unit or its AC power to rain or moisture.
- Do not alter the AC plug of the connected power adapter
- . Do not drip or splash liquids on the unit.
- · No user serviceable parts inside, refer servicing to qualified personnel only.
- WARNING: The unit must only be connected to a safety agency certified, regulated, power source (adapter), approved for use and compliant with applicable local and national regulatory safety requirements.
- Unplug the AC power adapter before cleaning the unit exterior. Use only a damp cloth
- for cleaning and then wait until the unit is completely dry before reconnecting it to power.
- Amplifiers and loudspeaker systems, and ear/headphones (if equipped) are capable
 of producing very high sound pressure levels which may cause temporary or permanent
 hearing damage. Use care when setting and adjusting volume levels during use.

THIS DEVICE COMPLIES WITH PART 15 OF FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFRENCE RECEIVED, INCLUDING INTERFRENCE THAT MAY CAUSE UNDESIRED OPERATION.

ADDITIONAL LANGUAGES

Manual available in additional languages at www.fender.com/support

SPECIFICATIONS

IMPEDANCES Input: 500kΩ Output: 470Ω
POWER SUPPLY 100mA min @ 9VDC regulated and

5.5 x 2.1 mm barrel connector (not included)

OVDC

DIMENSIONS 2.44" x 4.4" : WEIGHT 0.50 lbs (0.23

POWER REQUIREMENTS

2.44" x 4.4" x 2.2" (62mm x 111.8mm x 55.9mm) 0.50 lbs (0.23kg)

0.50 lbs (0.25k



Product specifications subject to change without notice



Tender

© FENDER MUSICAL INSTRUMENTS 2021

		广品中有	吉彻质时名	称及含重		
部件名称	有害物质					
	45 (Pb)	承 (Hg)	4% (Cd)	六价格 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
箱体	0	0	0	0	0	0
喇叭单元*	0	0	0	0	0	0
电子部分	X	0	X	0	0	0
接线端子	X	0	0	0	0	0
电线	X	0	0	0	0	0
附件	0	0	0	0	0	0

本表格依据 SJ/T 11364 的规定编制。

*产品含有喇叭单元时有效。

O: 表示该有毒有害物质在该部件所有均质材料中的含量均在 GB/T 26572 规定的限量要求以下。 X: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572 规定的限量要求。

注: 含有有害物质的部件由于全球技术发展水平限制而无法实现有害物质的替代。